The RITE Door®

New Push x Pull Operator
D3680 Series



For those applications where the lowest possible projection from the door is needed, Adams Rite introduces the new Push and Pull Operator for The RITE Door Integrated Door System. The push side operator projects only 5/8" from the door surface and the pull side is flush with the door surface. This new operator is ideal for elevator shaft smoke doors or where wall conditions will not allow a pocket to be built for standard lever trim. The pull side operator can be used as operating trim for a push side exit device. Available with all current RITE Door constructions and sizes.

Push x Pull Operator:

- Solid steel construction for durability in the most active openings
- Works with the Adams Rite patented top latch mechanism
- Smooth, ADA friendly operation

The RITE Door:

- Doors with the 3680 series are available in 16 or 18 gauge honeycomb, steel stiffened or temperature rise cores
- Door faces come primed, pre-finished or with HPL plastic laminates
- Up to 3 hour positive pressure label

ADAMS RITE
MANUFACTURING CO.

D3680 Series
New Operator for The RITE Door®

The RITE Door® is even more flexible with the addition of the Push x Pull operator option. Push x Pull operators are available in US26D or black powdercoat, and are listed by Warnock-Hersey for up to 3 hours under UL10-C.

The RITE Door was designed to be a complete door system and features pre-installed integrated hardware that ensures a fast, simple installation—reducing costs on new construction or retrofits and assuring perfect alignment and long lasting performance. The RITE Door is virtually maintenance free, and activation of the operator is smooth and quiet. The RITE Door is well known for its clean sight lines and comes in a wide variety of door and trim finishes. Options include exit device, vision lites, kick plates and a selection of hinges.

D3680 Series

- **Pull x Exit Device** **D3681**
- **Push x Pull** **D3682**
- **Pull Only** **D3683**
- **Push Only** **D3684**



Fire Ratings/ Maximum Door Sizes:

Steel Stiffened Construction

3-Hour Fire Rating:
Single Doors – 4'0" x 10'0"
Same Swing Pairs – 8'0" x 10'0"
Double Egress Pairs – 8'0" x 8'0"

20-, 45-, 60- & 90-Minute:
Single Doors – 4'0" x 10'0"
or 4'3" x 9'0"
Same Swing Pairs – 8'0" x 10'0"
or 8'6" x 9'0"
Double Egress Pairs – 8'0" x 10'0"
or 8'6" x 9'0"

Honeycomb Construction

3-Hour Fire Rating:
Single Doors – 4'0" x 8'0"
Same Swing Pairs – 8'0" x 8'0"
Double Egress Pairs – 8'0" x 8'0"

20-, 45-, 60- & 90-Minute:
Single Doors –4'3" x 9'0"
Same Swing Pairs –8'6" x 9'0"
Double Egress Pairs –8'6" x 9'0"

ADAMS RITE MANUFACTURING CO.
www.adamsrite.com

260 Santa Fe Street, Pomona, CA 91767 • 800-872-3267 FAX 800-232-7329
"ADAMS RITE" and are registered trademarks of ADAMS RITE MANUFACTURING CO, Pomona, CA
©2005 ADAMS RITE MANUFACTURING CO. • Rev. 1/2005 • PRINTED IN U.S.A.