
1700, 1800, 1900 Series Exit Devices

Classic Product

Certification & Compliance:

- ANSI/BHMA A156.3, Grade 1
- Underwriters Laboratories (UL and CUL) listed for accidoors

BHMA CERTIFIED
Be Safe. Be Secure. Be Certified.



1800
Rim Exit Device
ANSI Type 1

1700
Vertical Rod Exit Device
ANSI Type 2

1900
Mortise Exit Device
ANSI Type 1

General Specifications:

	1700	1800	1900
Chassis	Pressure formed non-ferrous alloy	Pressure formed non-ferrous alloy	Pressure formed non-ferrous alloy
Chassis and end covers	Cold drawn brass, bronze or stainless steel	Cold drawn brass, bronze or stainless steel	Cold drawn brass, bronze or stainless steel
Door Thickness	1-3/4" (44.45mm) standard, available for thick doors	1-3/4" (44.45mm) standard, available for thick doors	1-3/4" (44.45mm) standard, available for thick doors
Handing	Handed. Specify LHRB or RHRB	Handed. Specify LHRB or RHRB	Handed. Specify LHRB or RHRB
Dogging	Allen type only.	Allen type only.	Allen type only.
Top/Bottom Bolts	Brass	N/A	N/A
Latchbolt	N/A	Stainless steel, 5/8" (15.875mm) throw	Brass, 3/4" (19.05mm) throw
Crossbar Arms	Forged brass and stainless steel	Forged brass and stainless steel	Forged brass and stainless steel
Crossbar	1" (25.40mm) brass, bronze and stainless steel tubing, .062" (1.5875mm) thick	1" (25.40mm) brass, bronze and stainless steel tubing, .062" (1.5875mm) thick	1" (25.40mm) brass, bronze and stainless steel tubing, .062" (1.5875mm) thick
Crossbar projection	4-1/2" (114.3mm) neutral, 2-3/4" (69.85mm) depressed	4-1/2" (114.3mm) neutral, 2-3/4" (69.85mm) depressed	4-1/2" (114.3mm) neutral, 2-3/4" (69.85mm) depressed
Opening Height	90" (2286.00mm) standard	N/A	N/A
Fire Exit Hardware-up to:	4' x 7'2" single door 8' x 7'2" pairs of doors	4' x 7'2" single door 8' x 7'2" pairs of doors with S21 mullion	4' x 7'2" single door 8' x 7'2" pairs of doors(with 1700-FR)
Trim	See trim pages 119, 120	See trim pages 119, 120	See trim pages 119, 120
Finishes	US3, US4, US10, US10B, US32, US32D	US3, US4, US10, US10B, US32, US32D	US3, US4, US10, US10B, US32, US32D

How to Order:

Example: To order....
Specify:
Standard:

18	08	SL	26D	32D	RR	xxx
Series	Function	Outside Trim (If Applicable)	Outside Finish	Push Bar Finish	Handing	Options (If Required)

ARROW LOCK & DOOR HARDWARE
ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions

1000, 3000, 4000 Series Exit Devices

Classic Product

Arrow 1000, 3000 & 4000 Series Exit Device Trim:

Optional Slip-Clutch Lever Design

- Optional slip-clutch is built in beneath security collar added to shank of lever.
- Available for use with SL88, SL33 and SL08 exit device trim for 1000 and 3000 Series Exit Devices. (Not available for S1150 or S1250 Series devices.)
- ♿

Vandal-resistant slip-clutch lever releases when excessive force is applied without retracting latch. Easily reset by returning lever to horizontal position.

Exit Device Type:

ANSI TYPE	ARROW DEVICE	
Type 1	Rim	S1250, 1800, 3800
Type 2	Surface Vertical Rod	S1150, 1700, 3700
Type 3	Mortise	1900, 3900
Type 4	Narrow Stile Rim	4800
Type 6	Narrow Stile Concealed Vertical Rod	4600
Type 8	Metal Door Concealed Vertical Rod	3600
Type 10	Narrow Stile Mortise	4900
Type 22	Removable Mullion	S20, S21

Exit Device Function:

ANSI	ARROW FUNCTION	
01	Exit only; no outside trim	01, 03
02	Entry by trim when actuating bar is locked	01, 02, 03
03	Entry by trim when latchbolt retracted by key. Key removable only when trim is locked.	03
05	Entry by thumbpiece when thumbpiece locked/unlock by key.	05
05A	Entry by thumbpiece; thumbpiece always operative, no outside cylinder.	5A
08	Entry by knob/lever; outside key locks, unlocks knob/lever.	08
08A	Entry by knob/lever; outside knob/lever always operative.	08A
11	Entry by auxiliary control turnpiece key locks, unlocks control.	11
12	Entry by auxiliary control turnpiece only when released by turning key. Key removable only when locked.	12

Exit Device Trim Functions:

Function	1700/1700-FR	1800/1800-FR	1900/1900-FR
02*	SP, SS, SB, SN	SP, SS, SB, SN, SL	SP, SS, SB, SN, SL
03	N/A	SP, SS, SB, SN, SL	SP, SS, SB, SN, SL
05	SP, SS, SB, SN	SP, SS, SB, SN	SP, SS, SB, SN
05A	SP, SS, SB, SN	SP, SS, SB, SN	SP, SS, SB, SN
08	SL	SL	SL
08A	SL	SL	SL
11	S311	N/A	N/A
12	S312	N/A	N/A

Function	3600/3600-FR	3700/3700-FR	3800/3800-FR	3900/3900-FR
02*	SL	SP, SS, SB, SN, SL	SP, SS, SB, SN, SL	SP, SS, SB, SN, SL
03	N/A	N/A	SP, SS, SB, SN, SL	SP, SS, SB, SN, SL
05	N/A	SP, SS, SB, SN	SP, SS, SB, SN	SP, SS, SB, SN
05A	N/A	SP, SS, SB, SN	SP, SS, SB, SN	SP, SS, SB, SN
08	SL	SL	SL	SL
08A	SL	SL	SL	SL
11	S411	S311	N/A	N/A
12	S412	S312	N/A	N/A

Function	4600/4600*-FR	4800	4900/4900-FR
02*	SL	SS, SL	SS, SN, SL
03	N/A	SS, SL	SS, SN, SL
05	N/A	N/A	SS, SN
05A	N/A	N/A	SS, SN
08	SL	SL	SL
08A	SL	SL	SL
11	S511/UL-S411	N/A	N/A
12	S512/UL-S412	N/A	N/A

***02 not available fire rated.**

Order Example:

Example: To order.
Specify:
Standard:

38	88	SL	26D	F	32D	RR	xxx
Series	Function	Outside Trim (If Applicable)	Outside Finish	Rail Size	Push Bar Finish	Handing	Options (If Required)

ASSA ABLOY, the global leader in door opening solutions


ARROW LOCK & DOOR HARDWARE
ASSA ABLOY

Mullions & Accessories Series Exit Devices

Mullions & Accessories:

S20






Removable Mullion - S20
- Prime Coated aluminum
- 96" standard, 120" available
- Funished standard with top retainer (S10) and bottom retainer (S11)

S21






Removable Mullion - S21
- U.L. and C.U.L. Labeled for use with 3 hour fire doors.
- 2" x 3" channel iron;
- 96" standard, 120" available
- Furnished standard with malleable iron top retainer (S88) and bottom retainer (S89).
- Lengths from 97" to 120" do not carry U.L. fire label.

S20-N

S91



S92




S20-N
- Prime coated aluminum
- 96" standard, 120" available
- For use with narrow stile exit devices.
- Includes mullion, two #S55 strikes, two #S90 stabilizers, #S91 top bracket, #S92 bottom bracket.



S3000 Dummy Rail
A non-functioning rail assembly for use on double doors. Matches S3000 and S4000 series exit devices. Available in sizes 24 (for 24"-29" doors), 36 (for 30"-36" doors), 48 (for 37"-48" doors). Bars can be cut down in the field. For stile width under 4-1/2", specify next larger size. Available in finishes – 3, 4, 10, 10B, 32, 32D, AL, BRZ.



Cylinder Dogging Rail
- Optional cylinder dogging available



VRX-18 Rod Extension
- Prime Coated aluminum
- 96" standard, 120" available
- Furnished standard with top retainer (S10) and bottom retainer (S11)

BHMA CERTIFIED
Be Safe. Be Secure. Be Certified.

Mullions:


Description	Part No.
Removable mullion - 96"	S20
Removable Mullion - 120"	S20-120
Key removable mullion - 96", less cylinder	S20-K
Removable mullion for narrow stile - 96"	S20-N
Removable mullion for narrow stile - 120"	S20-N-120
Fire-rated removable mullion - 96"	S21
Fire-rated key removable mullion - 96", less cylinder	S21-K
Top retainer for S20	S10
Bottom retainer for S20	S11
Top retainer for S20-N	S91
Bottom retainer for S20-N	S92
Stabilizer for S20-N	S90
Top retainer for S21	S88
Bottom retainer for S21	S89

Fire Labeled Hardware Exit Devices


Selection chart for A through E labeled doors

For reference only. Refer to latest UL building materials list for complete information.


Application	Type	Narrow Device	Standard Device	Maximum Door Opening
Single Door	Rim	—	FS1250 1800-FR 3800-FR	4′0″ x 8′0″
	Mortise	4900-FR	1900-FR 3900-FR	4′0″ x 8′0″
Double Doors with S21 Mullion	Rim	—	FS1250 x FS1250 1800-FR x 1800-FR 3800-FR x 3800-FR	8′0″ x 8′0″
	Mortise x concealed vertical rod	4900-FR x 4600-FR	3900-FR x 3600-FR	8′0″ x 8′0″
Double Doors without Mullion	Mortise x surface vertical rod	—	1900-FR x 1700-FR 3900-FR x 3700-FR	8′0″ x 8′0″
	Two concealed vertical rod	4600-FR x 4600-FR	3600-FR x 3600-FR	8′0″ x 8′0″
	Two surface vertical rod	—	FS1150 x FS1150 1700-FR x 1700-FR 3700-FR x 3700-FR	8′0″ x 8′0″ (B-E)
Double Egress Doors	Two concealed vertical rod	4600-FR x 4600-FR	3600-FR x 3600-FR	8′0″ x 7′2″ (A) 8′0″ x 8′0″ (B-E)
	Two surface vertical rod	—	FS1150 x FS1150 1700-FR x 1700-FR 3700-FR x 3700-FR	8′0″ x 7′2″ (A) 8′0″ x 8′0″ (B-E)




S13 Bottom Strike
Stainless steel. Furnished with expansion shields. Stainless steel.




S14
For application to wood or hollow metal doors.




S15 Bottom Strike
Alternate for 1700-FS. For use on ½" threshold. Stainless steel. Furnished with expansion shields.




S24
F-400 Series standard for single door applications. Black nylon coated.




S45
Standard for F-S1700. Flush mounted. Stainless steel. Furnished with expansion shields.



S46 Bottom Strike
Standard for F-S1150, F-S3700. Flush mounted. Furnished with expansion shields. Stainless steel, black nylon coated.



S58 Bottom Strike
Alternate for F-S1150, 3700-FS. For use on ½" threshold. Stainless steel, nylon coated. Furnished with expansion shields.




646 Fire Rated Top Strike
Standard for FS1150 and 3700-FR. Surface applied. Nylon Coated

ASSA ABLOY, the global leader in door opening solutions

ARROW LOCK & DOOR HARDWARE
ASSA ABLOY

Exit Device Trim



SB



SB02




SB03



SB05A



SB05



SL



SL02



SL03/SL83



SL08A/SL88A




SL08/SL88


ASSA ABLOY, the global leader
in door opening solutions

ARROW LOCK & DOOR HARDWARE

ASSA ABLOY

Exit Device Trim






Auxiliary Outside Control



- **S311**–Use with S3700, FS3700, S1700, FS1700. Key locks or unlocks turn lever.
- **S312**–Use with S3700, FS3700, S1700, FS1700. Turn lever operative only with key in cylinder and turned.
- **S411**–Use with S3600, FS3600, FS4600. Key locks or unlocks turn lever.
- **S412**–Use with S3600, FS3600, FS4600. Turn lever operative only with key in cylinder and turned.
- **S511**–Use with S4600. Key locks or unlocks turn lever.
- **S512**–Use with S4600. Turn lever operative only with key in cylinder and turned.



SP



SP02/SP82




SP03/SP83



SP05A



SP05



SS



SS02/SS82




SS03/SS83



SS05A



SS05



SN



SN02/SN82



SN03/SN83



SN05A



SN05

ASSA ABLOY, the global leader in door opening solutions

ARROW LOCK & DOOR HARDWARE

ASSA ABLOY

Exit Device Selection Chart

For reference only. Refer to latest UL building materials list for complete information.

Application	Type	Narrow Stile Touch Bar	Standard Touch Bar	Crossbar
Single Door	Rim	4800	S1250, FS1250 3800, 3800-FR	1800, 1800-FR
	Vertical Rod	—	S1150, FS1150 3700, 3700-FR	Mortise
	Concealed Vertical Rod	4600, 4600-FR	3600, 3600-FR	Mortise
	Mortise	4900, 9600-FR	3900, 3900-FR	Mortise
Double Doors with Mullion	Rim	4800 x 4800 with S20-N mullion	S1250 x S1250 3800 x 3800 with S20 mullion FS1250 x FS1250 3800-FR x 3800-FR with S21 mullion	Mortise
Double Doors without Mullion	Concealed Vertical Rod	4600 x 4600 4600-FR x 4600-FR	3600 x 3600 3600-FR x 3600-FR	Mortise
	Vertical Rod	—	S1150 x S1150 FS1150 x FS1150 S3700 x S3700 3700-FR x 3700-FR	Mortise
	Vertical Rod x Mortise	—	3700 x 3700 3700-FR x 3700-FR	Mortise