N Series Deadlock

Arrow N Series Mortise deadlock security and mortise cylinder convenience with interchangeable core compatibility.



Certification & Compliance:





- Underwriters Laboratories (UL and CUL) listed for use on A label or lesser doors when used in conjunction with a rated primary latching device

General Specifications:

Housing – Heavy wrought steel with zinc dichromate finish.
Deadbolt – 1" (25.40mm), throw solid brass deadbolt with hardened steel pin.
Backset – 2-3/4" (69.85mm).
Doors – 1-3/8" (34.92mm) to 1-3/4" (44.45mm) thick standard.
Strikes – Supplied standard with #380 security strike for steel frame and #356 security strike for wood frame.
Handing – All functions are reversible.
Cylinder, Standard accepts standard 1-1/8" mortise cylinder –Solid brass, Arrow "A" keyway, drilled for 6 pins, pinned to 5. Supplied with two brass keys.
Cylinder Option – Accepts 6 or 7 pin, small format, interchangeable cores. Supplied less cores. Will accept Best™ or Falcon™ type cores. ASSA high security cylinders are available.

N Series Deadlock

Functions:

ARROW	ANSI		FUNCTION	DESCRIPTION/OPERATION
N40			Exit	Throw or retract bolt by thumbturn only.
N41	E06071		Single Cylinder	Throw or retract bolt by key outside, thumbturn inside.
N42	E06061		Double Cylinder	Throw or retract bolt by key either side.
N43	E06081		Single Cylinder	Throw or retract bolt by key one side.
N44	E06091		Classroom	Throw or retract bolt by key–Thumbturn retracts dead bolt, but does not project it.

Order Example:

Example: To order a N Series Single Cylinder Deadlock, Satin Chromium Plated finish with a 1-1/8" x 3-1/2" square corner strike, a 1" deadbolt, keyed different.

Specify:

Standard:	**N**	**41**	**26D**	**380**	**KA4**
	Series	Function	Finish	Strike	Keying Cylinder

Strikes

